

## SpectraColour™ Warranty

---

In Australia: CSR Building Products Limited ABN 55 008 631 356 trading as Viridian of 95 Greens Road, Dandenong, Victoria;  
In New Zealand: CSR Viridian (NZ) Ltd CN 6355 of 19 Gabador Place, Mt Wellington, Auckland;  
hereby provides the following Warranty in respect of Viridian SpectraColour™ Annealed, Toughened Glass and Heat-Strengthened Glass ("the Product") but excluding laminated SpectraColour glass products.

### 1. Period and Details

Subject to the provisions of this Warranty, Viridian warrants that the Product shall be, for a period of **7 years** from the date of manufacture, free of:

- Significant deterioration of painted coating under normal conditions and usage.
- Visible and visual defects, inclusions or faults which can be seen from a distance of at least 3 metres and which are not within the acceptable limits set out in the published specifications for the Product. (A copy of which is available on request.)
- Failure due to inadequacy of structural strength of the product as determined by AS1288 or NZS 4223 resulting from faulty materials up to the specified design wind pressure.

### 2. Warranty Coverage

This Warranty is to be read in conjunction with and subject to the Viridian "Terms and Conditions of Sale" in force at the time of sale.

So far as the law permits, this Warranty provides only for free replacement of the Product or refund of the original invoice value and under this Warranty, Viridian accepts no liability for personal injury, loss, claims, property damage, or labour, material or other costs (whether special or consequential or otherwise), howsoever caused or arising and whether direct or indirect.

### 3. Compliance to Standards

All Product conforms with the applicable Australian and New Zealand Standard AS/NZS 2208

### 4. Conditions

The Warranty is further subject to the following conditions:

- (a) That the Buyer acknowledges that the Product at the time of delivery was undamaged and free from any defects.
- (b) That the Product is protected from contact with wet cement, hard foreign objects, metals and materials likely to cause abrasive damage.
- (c) That the Product is protected from temperatures above 140 degrees Centigrade.
- (d) That installation and maintenance of the Product is entirely in accordance with Viridian's recommendations as published in Viridian literature and any specific correspondence pertaining to this installation, and the glass components are not damaged in any way before or during installation.
- (e) That the Product has been installed with the coated surface glazed to the inside of the building and not to the exterior of the building.
- (f) That the Product is not exposed to chemical fumes or gases other than those present in normal clear atmospheric air nor is subject to prolonged exposure to water or moisture, nor is exposed to radiation of any type other than normal sunlight.
- (g) That the Product is not subject or likely to be subject to stresses from any cause in excess of the stresses advised as acceptable in Viridian literature or in specific correspondence.
- (h) That any sealant or adhesive used in glazing is compatible with the coating.
- (i) Recommended cleaning and maintenance procedures are followed.
- (j) That the intended application has been brought to the attention of Viridian prior to order acceptance and heat soak treatment specified where recommended by Viridian has been undertaken